

# Thermometer hygrometer with Ethernet interface and relays, humidistat

code: H3530



Humidity, temperature, humidex Ethernet sensor with two relay outputs. Sensor H3530 is designed for online monitoring of temperature, relative humidity, humidex of air without aggressive substances. Three binary inputs to detection of two-states signals are the advantage. Other devices are controlled by two relay outputs.

High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Measured values are also converted to other humidity interpretation: humidex, dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.

### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

### Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
RELAY OUTPUTS	
Quantity	2
Maximal voltage	50 V
Maximal current	2 A
Maximal power	60 VA
BINARY INPUTS	
Quantity	3
Signal for binary inputy	dry contact, open collector or two-state voltage signal. Inputs are not galvanically isolated.
Minimum pulse duration on binary input	500 ms
Voltage across open contact	< 3,3 V
Low voltage level	0 to +0,5 V
High voltage level	+3,0 to +30 V

GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	internal temperature and humidity sensor
Acoustic alarm	from built-in beeper - switchable
Counted values	humidex, dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Output	Ethernet
Measuring interval	2 s
Range of humidity sensor temperature compensation	all temperature range
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail (SMTP authentication is supported), SNMP Trap, Syslog
Power	9-30 Vdc
Protection class	IP40
Dimensions	136 x 213 x 45 mm; stem length 75 mm
Weight	approx. 360 g
Warranty	3 years