

## CO2 concentration transmitter with two relay outputs

code: H5024



CO2 level transmitter with two output relays.

CO<sub>2</sub> sensors with relay or serial output (RS485/RS232) are designed for industrial environments as well as spaces where the sensor's appearance matters.

Selected models feature two relay outputs for alarm indication or control of external devices. Each relay can be assigned to a measured or calculated value, with configurable threshold, delay, hysteresis, and acoustic alarm. Controllers are equipped with a power relay (50 V / 2 A).

[Extended measuring range available for an additional charge](#)

- **Measuring range:** 0 to 10 000 ppm
- **Accuracy:** 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

### Technical data

CO2 SENSOR	
Measuring range	0 to 5000 ppm
Accuracy	±(50ppm +3% from reading) at 25°C and 1013hPa
Resolution	1 ppm
RELAY OUTPUTS	
Quantity	2
Maximal voltage	50 V
Maximal current	2 A
Maximal power	60 VA
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +60 °C
Channels	internal CO <sub>2</sub> sensor
Acoustic alarm	from built-in beeper - switchable
Power	9-30 Vdc
Protection class	IP30
Dimensions	136 x 150 x 45 mm
Weight	approx. 360 g
Warranty	3 years