

Temperature, humidity, CO2 and atmospheric pressure data logger with built-in sensors

code: U4440



Datalogger is designed to record temperature, humidity, atmospheric pressure and CO2. In case of exceeded set limits alarms are indicated by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via USB-C.

Recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

Possibility to [extend the measuring range](#) for an additional charge:

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Technical data

| | |
|-----------------------------|--|
| TEMPERATURE SENSOR | |
| Measuring range | -20 to +60 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 0 to 100 % RH |
| Accuracy | ± 1.8 % RH |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -60 to +60 °C |
| Accuracy | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution | 0.1 °C |
| CO2 SENSOR | |
| Measuring range | 0 to 5000 ppm |
| Accuracy | ±(50ppm +3% from reading) at 25°C and 1013hPa |
| Resolution | 1 ppm |
| ATMOSPHERIC PRESSURE SENSOR | |
| Measuring range | 700 to 1100 hPa |
| Accuracy | ±1.3 hPa at 23 °C from 800 to 1100 hPa |
| Resolution | 0.1 hPa |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -20 to +60 °C |

| | |
|------------------------------|--|
| Channels | internal sensor for temperature, humidity, CO ₂ and atmospheric pressure |
| Memory | 500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode |
| Recording interval | adjustable from 1 s to 24 h |
| Display and alarm refresh | adjustable 1 s, 10 s, 1 min |
| Recording mode | noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new |
| Real time clock | year, leap year, month, day, hour, minute, second |
| Power | battery SONY Lilon 5200mAh |
| Protection class | IP20 |
| Dimensions | 61 x 93 x 53 mm |
| Weight (including batteries) | approx. 250 g |
| Warranty | 3 years |