

IoT Wireless Temperature Sensor for 4 external Pt1000 probes with CINCH connector, powered by Sigfox

code: W0841E



The device measures the temperature from four external Pt1000 probe on the cable - you can [choose it from an optional accessory](#).

The measured values are sent in an adjustable time interval (10 min to 24 h) by radio transmission in the [Sigfox network](#) to the [COMET Cloud](#), from which the user can view them using a personal computer or mobile device.

The instrument can monitor up to 2 alarm limits of the each measured temperature channel. Exceeding these limits is indicated by sending an emergency message. [COMET Cloud](#) transmits this alarm message via e-mail to the selected user. The device is suitable for applications that tolerate the delay of information delivered by Sigfox (max. 10 min).

Highlights:

- wireless transmission of measured values and alarm states
- temperature measurement in up to four places for the price of one fee
- battery power (C size) with low battery indication (battery life 1 - 10 years)
- input for external power
- remote setting of the device from [COMET Cloud](#) (maximum once a day)
- IP20
- Traceable calibration certificate in accordance with EN ISO / IEC 17025

The availability of Sigfox network in a particular location

[Check your Sigfox network availability](#) before you buy your device. COMET devices in the Sigfox network can be used anywhere in the RC1 zone. Learn more about [Sigfox \(RC\) Radio Zones](#).

Technical data

TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-200 to +260 °C
Accuracy	±0.2 °C in the range -200 to +100 °C; ±0.2 % from reading from +100 to +260 °C
Resolution	0.1 °C
Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s)	10 minutes
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	4x external temperature probe; CINCH connector
Message transmission interval	adjustable 10 minutes, 20 minutes, 30 minutes, 1 hour, 3 hours, 6 hours, 12 hours, 24 hours
Operating frequency	868 MHz

Maximum transmission power	25mW
Sigfox radiation class	0U
Radio configuration zone	RC1 (operation is possible in Europe, Iran, Oman and South Africa)
Typical range of transmitter	50 km in the field, 3 km in the city
Power	Lithium battery 3.6 V, C size, capacity 8.5 Ah
Number of battery slots	1
Protection class	IP20
Dimensions	179 x 134 x 45 mm without connectors
Weight (including batteries)	350g
Warranty	3 years